


METALIZED POLYESTER FILM CAPACITOR

TYPE:MEY

Are constructed with special metalized polyester film dielectric, copper-ply leads, encapsulated in flame-retardant plastic case with epoxy resin sealed, in non-inductive type.

FEATURES:

- 10mm to 22.5mm lead pitch.
- Self-healing properties.
- High moisture resistance.
- Overtoltage stress withstanding.
- UL/CSA and European safety regulations class Y2.
(Meeting EN132 400 1994/IEC384-14 2nd 1993)
- Flame retardant plastic case and epoxy resin(UL-class 94V-0).



APPLICATIONS:

They are ideal for line-by-pass, across-the-line, antenna coupling, spark killer circuits, switching power supply and available for EMI filter application.

SPECIFICATION:

- | | |
|-------------------------------|--------------------------|
| 1. Operating temperature | : -40°C ~ +85°C |
| 2. Capacitance range | : .001uF ~ .047uF |
| 3. Capacitance tolerance | : J=±5%, K=±10%, M=±20%. |
| 4. Rated voltage (RV) | : 250VAC 50Hz ~ 60Hz |
| 5. Dissipation factor (DF) | : 1.0% max at 1KHz 25°C |
| 6. Testing voltage (TV) | : 1500vac 60sec |
| 7. Insulation resistance (IR) | : IR≥15000MΩ |

(measured at 100±15vdc 60sec at 25°C)

DIMENSIONS:

unit:mm

RV	250VAC				
size	W	H	T	P	dφ
cap.	±0.5	±0.5	±0.5	±0.5	±0.05
.0010	13.0	11.0	5.0	10.0	0.6
.0012	13.0	11.0	5.0	10.0	0.6
.0015	13.0	11.0	5.0	10.0	0.6
.0018	13.0	11.0	5.0	10.0	0.6
.0022	13.0	11.0	5.0	10.0	0.6
.0027	13.0	11.0	5.0	10.0	0.6
.0033	13.0	12.0	6.0	10.0	0.6
.0039	13.0	12.0	6.0	10.0	0.6
.0047	13.0	12.0	6.0	10.0	0.6
.0056	18.0	12.0	6.0	15.0	0.8
.0068	18.0	12.0	6.0	15.0	0.8

RV	250VAC				
size	W	H	T	P	dφ
cap.	±0.5	±0.5	±0.5	±0.5	±0.05
.0082	18.0	13.5	7.5	15.0	0.8
.010	18.0	13.5	7.5	15.0	0.8
.012	18.0	13.5	7.5	15.0	0.8
.015	18.0	14.5	8.5	15.0	0.8
.018	26.5	15.0	6.0	22.5	0.8
.022	26.5	15.0	6.0	22.5	0.8
.027	26.5	16.0	7.0	22.5	0.8
.033	26.5	16.0	7.0	22.5	0.8
.039	26.5	17.5	8.5	22.5	0.8
.047	26.5	19.0	10.0	22.5	0.8

Please contact us for special case or items not listed.

CAPACITOR TYPE	VOLTAGE CODE	TOLERANCE CODE	CAPACITANCE (PF)	LEAD STYLE	LEAD SPACING
M E F	4 0 0	K	1 5 3	B	1 0

TYPE	CODE	RATED VOLTAGE
MMT		
EM7	050	50 Vdc
MEF	063	63 Vdc
DME	100	100 Vdc
MEM	125	125 Vdc
MEA	160	160 Vdc
MET	200	200 Vdc
MEY	250	250 Vdc
PEI	400	400 Vdc
PEN	500	500 Vdc
MPP	600	600 Vdc
MPM	630	630 Vdc
MPT	800	800 Vdc
MPA	102	1000 Vdc
MPX1	152	1500 Vdc
MPX2	162	1600 Vdc
MY2	252	2500 Vdc
PPN	1AC	125 VAC
PPT	2AC	250 VAC
PPS	AC	275 VAC
X1/Y1	3BC	300 VAC
X1/Y2	3AC	310 VAC
AME	2CC	350 VAC
MEV	4AC	400 VAC
QPC	4BC	450 VAC
AMP		

CODE	TOLERANCE
G	±2%
J	±5%
K	±10%
M	±20%

CODE	CAPACITANCE
102	0.001µF 1,000PF
472	0.0047µF 4,700PF
103	0.01µF 10,000PF
153	0.015µF 15,000PF
334	0.33µF 330,000PF
104	0.1µF 100,000PF
684	0.68µF 680,000PF
105	1.0µF 1,000,000PF
475	4.7µF 4,700,000PF
186	18µF 18,000,000PF

CODE	RATED VOLTAGE
3	3.0 mm
3.5	3.5 mm
4	4.0 mm
5	5.0 mm
6	6.0 mm
7	7.0 mm
7.5	7.5 mm
8	8.0 mm
9	9.0 mm
10	10.0 mm
15	15.0 mm
20	20.0 mm
22.5	22.5 mm
27.5	27.5 mm

CODE	LEAD PACKING STYLE	CODE(7) SPECIFIED AS:
A	TAPE / AMMO	LEAD SPACING(P)
B	STANDARD BULK	LEAD SPACING (P)
T	TAPE & REEL STANDARD LEAD SPACING ON TAPED PART IS 5mm SPECIAL 7.5mm AND 10mm SPECIFY LEAD SPACING	NOT APPLICABLE IF STANDARD
TA	AXIAL LEAD TAPING	NOT APPLICABLE
C	CUTTING BULK NOTE LEAD SPACING IS PART OF THE DESCRIPTION	LEAD LENGHT
F	FORMING BULK	LEAD SPACING (P)
K	KINKED BULK	LEAD SPACING (P)
X	SPECIAL LEAD CONFIGURATION	CONSULT FACTORY

FORMING AND CUTTING

(A) CUTTING STYLE	(B) KINK STYLE	(C) FORMING STYLE	(D) CUSTOM-MADE
			<p>Technical expertise available to design and produce items of special requirements to customers satisfaction.</p>

(UNITS: mm)